MI 6123 (US).	 Response	 Page 2
1411 O 1 E O 1 O O 7 .	 , tooponee	

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claims 1-9. (cancelled).

- 10. (previously presented) A concentrate comprising (percentages by weight):
 - A) from 40% to 95% of a composition relative to the total weight of A) comprising:
 - 1) from 10% to 35% of polybutene-1, wherein the polybutene-1 comprises a melt flow rate ranging from 100 to 1000 g/10 min., measured at 190°C at 2.16 kg;
 - 2) from 90% to 65% of polypropylene; and
 - B) from 5% to 60% of one or more additives.
- 11. (previously presented) The concentrate according to claim 10, wherein the concentrate comprises from 50% to 95% by weight of the composition relative to the total weight of A).
- 12. (previously presented) The concentrate according to claim 10, wherein the concentrate comprises from 60% to 80% by weight of the composition relative to the total weight of A).
- 13. (previously presented) The concentrate according to claim 10, wherein the composition comprises from 25% to 35% by weight of polybutene-1.
- 14. (previously presented) The concentrate according to claim 10, wherein the composition comprises from 30% to 35% by weight of polybutene-1.
- 15. (previously presented) The concentrate according to claim 10, wherein the composition comprises from 75% to 65% by weight of polypropylene.
- 16. (previously presented) The concentrate according to claim 10, wherein the composition comprises from 70% to 65% by weight of polypropylene.

- 17. (previously presented) The concentrate according to claim 10, wherein the composition comprises from 5% to 50% by weight of one or more additives.
- 18. (previously presented) The concentrate according to claim 10, wherein the composition comprises from 20% to 40% by weight of one or more additives.
- 19. (previously presented) The concentrate according to claim 10, wherein the polybutene-1 is a linear, semicrystalline and highly isotactic homopolymer.
- 20. (previously presented) The concentrate according to claim 10, wherein the polypropylene is isotactic polypropylene having an index of isotacticity greater than or equal to 90.
- 21. (previously presented) The concentrate according to claim 10 for dispersing one or more additives in at least one polyolefin.
- 22. (previously presented) Polyolefinic articles comprising the concentrate of claim 10, wherein the concentrate is blended with at least one polyolefin and then processed.
- 23. (previously presented) Coloured polypropylene fibres comprising the concentrate of claim 10, wherein the concentrate is blended with at least one polyolefin and then spun.
- 24. (previously presented) A polyolefinic composition for preparing concentrates of additives, comprising (percentages by weight):
 - a) from more than 10% to 35% of polybutene-1 comprising a melt flow rate ranging from 100 to 1000 g/10 min., measured at 190°C at 2.16 kg; and
 - b) from less than 90% to 65% of polypropylene.
- 25. (previously presented) The polyolefinic composition of claim 24 comprising from 25% to 35% by weight of polybutene-1.
- 26. (previously presented) The polyolefinic composition of claim 24 comprising from 30% to 35% by weight of polybutene-1.
- 27. (previously presented) The polyolefinic composition of claim 24 comprising from 75% to 65% by weight of polypropylene.
- 28. (previously presented) The polyolefinic composition of claim 24 comprising from 70% to 65% by weight of polypropylene.

- 29. (previously presented) The concentrate of claim 10, wherein the polybutene-1 comprises a melt flow rate ranging from 100 to 400 g/10 min., measured at 190°C at 2.16 kg.
 - 30. (canceled)

Ø

- 31. (canceled)
- 32. (canceled)
- 33. (previously presented) The concentrate of claim 10, wherein the additives are selected from at least one pigment, colorant, or mixture thereof.
 - 34. (cancelled)
- 35. (currently amended) A concentrate [according to claim 34] consisting essentially of (percentages by weight):
 - A) from 40% to 95% of a composition relative to the total weight of A) consisting essentially of:
 - 1) from 10% to 35% of polybutene-1, wherein the polybutene-1 comprises a melt flow rate ranging from 100 to 1000 g/10 min., measured at 190°C at 2.16 kg;
 - 2) from 90% to 65% of polypropylene; and
 - B) from 5% to 60% of one or more additives.